

APS 60 & 100 TRAILER SPECIFICATION

TANDEM AXLE TRAILERS

Designed specifically for the Altorfer APS 60 and APS 100 rental generator sets. Each trailer is of rugged, heavy duty steel construction suitable for the wide variety of difficult operating conditions. Finished in gloss black urethane enamel ensuring durability and corrosion resistance. These rugged trailers matched with an Altorfer generator set driving increased value in the rental and used market.

CONSTRUCTION

- Heavy duty steel frame construction
- Frame Rails: C6 x 8.2# Gr 50
- Cross members: Formed plate .250 Gr 36
- Tongue: Frame rails cold formed and reinforced
- Fenders: Smooth steel 12 Ga Gr 36
- Bumper: Formed sheet 7 Ga Gr 36

SAFETY

- 2 x 3/8" heavy duty safety chains grade 70 w/ 3/8" snap hook
- Emergency breakaway: Rechargeable gel cell w/self-diagnostic battery level meter
- Federal DOT/SAE approved sealed beam LED lights
- Color coded 14 Ga sealed modular wiring harness w/ 7 pin connector
- Anti-skid tape on top of fenders

DESIGN FEATURES

- Designed for APS 60 and APS 100
- Tandem axle
- GVWR: 4,527 Kg (9,980 Lbs)
- GAWR 4,608 Kg (10,160 Lbs)
- 3" Towing eye (20,000# GTW) with adjustable height
- Tongue jack: 7,000# top wind w/ drop leg
- Overall dimensions: 205.30"L x 82.00"W x 31.00" H @ fender

RUNNING GEAR

- Axles: 6,000# drop
- Axle Rating: 2,722 Kg (6,000 Lbs)
- Rim Size: 15" 5,200# capacity, 6-bolt on 5.50 bolt circle white mod
- Tire size: ST225/75R – Load Range D
- Tire Pressure - 2,540# load rating single @ 50psi
- Brakes: Electric on both axles

FINISH

- Extremely durable and corrosion resistant
- Complete trailer is steel grit blasted to remove all weld scale and for superior paint adhesion
- Primed with 2 coats of rust-prohibitive primer
- Painted with 3 coats of high-gloss urethane topcoat
- All Hentzen Coatings brand, all electrostatically applied